

LITHIUM 3.6V 1500MA 2/3AA 14.1X33.3MM

€ 7,95

Excl. BTW: € 6,57

## Afbeeldingen



## Beschrijving

### Features

- High energy density

- Long term high performance
- Major improvement of voltage delay at the start of discharge at medium current levels
- Intermittent discharge at medium current levels
- Wide temperature range from -55°C to +85°C

## Technical Specifications

System:	LiSOCl <sub>2</sub>
Nominal Voltage:	3,6V
Temperature Range:	-55...+85°C

Part No.	Cell Size	C <sub>N</sub> [mAh]	I <sub>N</sub> [mA]	I <sub>max.</sub> [mA]	I <sub>p</sub> [mA]
SL-750/S	1/2AA	1100	1	50	100
SL-750/T	1/2AA	1100	1	50	100
SL-750/P	1/2AA	1100	1	50	100
SL-761/S	2/3AA	1500	1,3	75	150
SL-761/T	2/3AA	1500	1,3	75	150
SL-761/P	2/3AA	1500	1,3	75	150
SL-760/S	AA	2200	2	100	200
SL-760/T	AA	2200	2	100	200
SL-760/P	AA	2200	2	100	200

## Productinformatie

Artikelnummer	SL761/S
Merk	TADIRAN

