

LITHIUM ACCU 3V 20MA LIGGEND 12X2MM VANADIUM-PENTOXIDE-LITHIUM

€ 4,79

Excl. BTW: € 3,96

Afbeeldingen



Beschrijving

Features

- As a backup in computers, fax machines and mobile phones
- Low discharge current of 2% per year
- After backup application rechargeable again

Technical Specifications

Part Nr.	U_N	C_{typ}	I_d	D	H	Weight	T_b
	[V]	[mAh]	[mA]	[mm]	[mm]	[g]	[°C]
VL1220_	3	7	0,03	12,5	2	0,8	-20...+60
VL2020_	3	20	0,07	20	2	2,2	-20...+60
VL2320_	3	30	0,1	23	2	2,8	-20...+60

VL2330_	3	50	0,1	23	3	3,7	-20...+60
---------	---	----	-----	----	---	-----	-----------

U_N = Rated Voltage, C_{typ} = Capacitance, T_{yp} , I_D = Continuous Discharging Current, D = Diameter, H = Height, T_b = Temperature Range, Nominal Capacity is Based on Standard Drain I_D and Cut Off Voltage Down to 2,5V at 20°C

Charging Data

Constant Charging Voltage:	3,4V±0,15V
Charging Current, Max	
VL1220_:	0,5mA
VL2020_:	1,5mA
VL2320_:	2,0mA
VL2330_:	2,0mA
Cycle Life	
At 10% Discharge Depth, Approx.:	1000
At 50% Discharge Depth, Approx.:	100

Productinformatie

Artikelnummer	VL2020/HFN
Merk	PANASONIC

