

## LI-ION PACK 10,8V/5,2AH 3SP2 PLAT 3 X 2 CEL SERIE/PARALLEL

€ 99,50

Excl. BTW: € 82,23

### Afbeeldingen



### Beschrijving

#### Features

- Shrinks in shrink tubing
- Stranded wire connection for easy plug mounting
- Protective circuit (safety board) protects against overcharging, overload, short circuit and deep discharge
- Have a valid UN38.3 transport test
- Little self-discharge
- Thermally stable
- High power density

#### Technical Specifications

Part No.	Series / Parallel	Number of Cells
LI03652	1S1P	1
LI07226	2S1P	2

LI11126	3S1P	3
LI14426P	4S1P	4
LI03652	1S2P	2
LI03678	1S3P	3
LI14452	4S2P	8
LI14426V	4S1P	4
LI07252	2S2P	4
LI10852	3S2P	6

Part No.	C <sub>nom.</sub> [Ah]	R <sub>I max.</sub> [mOhm]	U <sub>R</sub> [V]	U <sub>C</sub> [V]	U <sub>D</sub> [V]	I <sub>C nom.</sub> [C]	I <sub>L max.</sub> [A]	I <sub>D max.</sub> [A]
LI03626	2,6	100	3,6	4,2	2,75	0,5	2,5	2,5
LI07226	2,6	140	7,2	8,4	5,5	0,5	-	5
LI11126	2,6	240	11,1	12,6	8,25	0,5	2,6	5
LI14426P	2,6	320	14,4	16,8	11	0,5	-	4
LI03652	5,2	80	3,6	4,2	2,75	0,5	3	3
LI03678	7,8	70	3,6	4,2	2,75	-	3	3
LI14452	5,2	180	14,4	16,8	11	0,5	-	4
LI14426V	2,6	300	14,4	16,8	11	0,5	-	4
LI07252	5,2	120	7,2	8,4	-	0,5	5	5
LI10852	5,2	120	10,8	12,6	8,25	-	5	5

C<sub>nom.</sub> = Rated Capacitance, nominal, R<sub>I</sub> = Inner Resistance, max., U<sub>R</sub> = Rated Voltage, U<sub>C</sub> = Charging Voltage, U<sub>D</sub> = Discharging Voltage, I<sub>C nom.</sub> = Charging Current, nominal (C-rate), I<sub>C max.</sub> = Charging Current, max., I<sub>D max.</sub> = Discharging Current, max.

#### Application temperature

Part No.	Charging	Discharging	Storage <sup>1)</sup>	Storage <sup>2)</sup>
----------	----------	-------------	-----------------------	-----------------------

LI03626	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C
LI07226	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C
LI11126	0...+45°C	-20...+60°C	-20...+45°C	-20...+30°C
LI14426P	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C
LI03652	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C
LI03678	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C
LI14452	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C
LI14426V	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C
LI07252	0...+45°C	-20...+60°C	-	-20...+30°C
LI10852	0...+45°C	-20...+60°C	-20...+45°C	-20...+20°C

<sup>1)</sup>up to 3 Months, <sup>2)</sup>up to 1 Year

## Productinformatie

Artikelnummer	LI10852
Merk	ANSMANN

