

ATON 30/250-700 LED DRIVER 2-54VDC 250-700MA 30W 144X30X21MM

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



Model	Input Voltage (V)	Input Current (mA)	Output Voltage (V)	Output Current (mA)	Power (W)	Efficiency (%)	Temp. Rise (°C)	Max. Temp. (°C)
ATON 30/250-700	12	1000	250	1000	30	85	10	100
ATON 30/250-700	18	667	250	1000	30	85	10	100
ATON 30/250-700	24	500	250	1000	30	85	10	100
ATON 30/250-700	30	400	250	1000	30	85	10	100
ATON 30/250-700	36	333	250	1000	30	85	10	100
ATON 30/250-700	42	286	250	1000	30	85	10	100
ATON 30/250-700	48	250	250	1000	30	85	10	100
ATON 30/250-700	54	222	250	1000	30	85	10	100

Beschrijving



EIJLANDER
the best in electronics!

Features

- Multipower driver supplied with dip-switch for the selection of the output current.
- IP20 independent driver, for indoor use (ATON).
- Class I protection against electric shock for direct or indirect contact (ATON).
- Driver for built-in use (ATON BI).
- It can be used for lighting equipment in protection class I (ATON BI).
- Active Power Factor Corrector.
- Current regulation $\pm 5\%$ including temperature variations.
- Input and output terminal blocks on the opposite side (wire cross-section up to $1,5 \text{ mm}^2$ / AWG15).
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm (ATON).
- Driver can be secured with slot for screws.
- Protections:
 - against overheating and short circuits;
 - against mains voltage spikes;
 - against overloads.
- Thermal protection = C.5.a.

Productinformatie

Artikelnummer	127360BIS
Merk	TCI
Is on Sale	Nee

