


INSTELPOT 1 SLAG LIGGEND 1K

€ 0,90

Excl. BTW: € 0,74

Afbeeldingen



Beschrijving

Features

- Excellent high temperature, high voltage and current ratings
- For professional applications

Electrical Specifications

| | |
|--|---------------------------------|
| Taper: | Linear |
| Power Rating ($T_u = 70^{\circ}\text{C}$): | 0,5W |
| Operating Voltage, Max.: | 200V DC |
| Resistance Tolerance: | $\pm 10\%$ |
| Residual Resistance, Min.: | 20 Ω or $1\% \times R_n$ |

| | |
|---------------------------|--------------|
| Contact Resistance, Min.: | 30hmor 2%xRn |
| Temperature Range: | -55...+125°C |

Mechanical Specifications

| | |
|------------------|-------|
| Rotation | |
| Mechanical: | 260° |
| Electrical: | 220° |
| Stop Torque: | 50mNm |
| Operating Force: | 20mNm |

Dimensions

| | |
|--------------------------|---------------|
| Length x Width x Height: | 7,0x7,0x5,8mm |
| Pitch: | 5x2,5mm |

Productinformatie

| | |
|---------------|--------|
| Artikelnummer | K001EP |
| Merk | COPAL |

