

POTMETER MONO LIN 6MM AS 50K 1W IP64

€ 12,50

Excl. BTW: € 10,33

Afbeeldingen



Beschrijving

Technical Specifications

| | |
|--|------------------------------------|
| Power Rating ($T_U = 70^\circ\text{C}$): | 1W |
| Hold-off Voltage: | 350V |
| Dielectric Strength (RMS): | 1500V |
| Insulation Resistance, Min.: | $10^6\text{M}\Omega$ |
| Standard Tolerance: | $\pm 10\%$ |
| Resistive Element: | Cermet |
| End Resistance (Typ.): | 20 Ω |
| Electrical Travel: | $270^\circ \pm 10^\circ$ |
| Mechanical Travel: | $300^\circ \pm 5^\circ$ |
| Operating Torque, Max.: | 0,4...1,8Ncm |
| Stop End Torque, Max.: | 80Ncm |
| Temperature Range: | $-55...+125^\circ\text{C}$ |
| Temperature Coefficient (Typ.): | $\pm 150\text{ppm}/^\circ\text{C}$ |
| Climatic Category: | 55/125/56 |
| Sealing: | IP64 |

| Part Nr. | R | $P_{\text{Max.}}$ | $U_{\text{Max.}}$ | $I_{\text{Max.}}$ |
|----------|----------|-------------------|-------------------|-------------------|
| | Ω | [W] | [V] | [mA] |
| E100P11 | 100 | 1 | 10 | 100 |
| E500P11 | 500 | 1 | 22,4 | 44,7 |
| K001P11 | 1K | 1 | 31,6 | 31,6 |
| K005P11 | 5K | 1 | 70,7 | 14,1 |
| K010P11 | 10K | 1 | 100 | 10,0 |
| K050P11 | 50K | 1 | 224 | 4,47 |
| K100P11 | 100K | 1 | 316 | 3,16 |
| K500P11 | 500K | 0,25 | 350 | 0,7 |

| | | | | |
|---------|----|------|-----|------|
| MO01P11 | 1M | 0,12 | 350 | 0,35 |
|---------|----|------|-----|------|

R = Resistance, P_{Max.} = Power, Max. (+70°C), U_{Max.} = Operating Voltage, Max., I_{Max.} = Transmission Current, Max.

Norms

CECC41000

Productinformatie

| | |
|---------------|---------|
| Artikelnummer | KO5OP11 |
| Merk | VISHAY |

