

**DC MAXI JOLLY LED DRIVER 74VDC MAX 350-1050MA 50W
124,5X79X22MM DIMBAAR 1-10V & PUSH**


€ 53,49

Excl. BTW: € 44,21

Afbeeldingen



| Model | Output Voltage (V) | Output Current (mA) | Power (W) | Dimensions (mm) | Weight (g) | Material |
|---------------------|--------------------|---------------------|-----------|-----------------|------------|----------|
| DC MAXI JOLLY US | 74 | 350-1050 | 50 | 124,5 x 79 x 22 | 10,5 | PC |
| DC MAXI JOLLY US BI | 74 | 350-1050 | 50 | 124,5 x 79 x 22 | 10,5 | PC |



Beschrijving

Features

- Multipower driver supplied with dip-switch for the selection of the output current.
- IP20 independent driver, for indoor use (DC MAXI JOLLY US).
- Class II protection against electric shock for direct or indirect contact (DC MAXI JOLLY US).
- Driver for built-in use (DC MAXI JOLLY US BI).
- It can be used for lighting equipment in protection class I and II (DC MAXI JOLLY US BI).
- Active Power Factor Corrector.
- Analogical input (NTC) for thermal sensor connection.
- Auxiliary output 12 V max. 100 mA.
- Current regulation $\pm 5\%$ including temperature variations.
- Input and output terminal blocks on the same side (wire cross-section up to 2,5 mm² / AWG13).
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm (DC MAXI JOLLY US).
- Protections:
 - against overheating and short circuits;
 - against mains voltage spikes;
 - against overloads.
- Thermal protection = C.5.a.

Productinformatie

| | |
|---------------|--------|
| Artikelnummer | 127411 |
| Merk | TCI |
| Is on Sale | Nee |

