

NETFILTER RFI IEC 1A 230V SCHAKELAAR EN ZEKERING FASTON 6.3MM

€ 48,50

Excl. BTW: € 40,08

Afbeeldingen



Beschrijving

Features

- Filter built in a metal housing with integrated power line connector, fuse holder and 2-pole, non-illuminated line switch
- Fuse holder for two fuses 5x20mm
- Flange mounting from front or rear side
- PCB mounting and faston plug terminal 6,3x0,8mm added

Technical Specifications

Continuous Operating Voltage, Max.:	250V, 50/60Hz
Dielectric Strength, 2s	
Line To Ground:	2kV AC

Line To Ground B-Type:	2,5kV AC
Line To Neutral:	0,76kV AC
Temperature Range:	-25...+85°C
Protection Class Front Side:	IP40
Rocker Switch:	
Ratings:	10 (4)A/250V AC
Inrush Current:	82A

Part Nr.	I_R	L1	L2	C_X	C_{Y1}	C_{Y2}	I_L
	[A]	[mH]	[mH]	[nF]	[nF]	[nF]	[mA]
FN9290-1F	1	10,9	10,9	220	1,5	0,47	0,28
FN9290-2F	2	4,4	4,4	220	1,5	0,47	0,28
FN9290-4F	4	1,7	1,7	220	1,5	0,47	0,28
FN9290-6F	6	0,78	0,78	220	1,5	0,47	0,28
FN9290-10F	10	0,32	0,32	220	1,5	0,47	0,28

I_R = Rated Current, at 40°C, L = Inductance, I_L = Leakage Current, Max. at 250V, 50Hz

Approvals



Productinformatie

Artikelnummer	FN9290-1F
Merk	SCHAFFNER

