

**PIEZO 12VDC/18MA/3.5KHZ/95DB MET 8 X LED GEEL KONTANTE TOON5
STUKS**

€ 32,95

Excl. BTW: € 27,23

Afbeeldingen



Beschrijving

Features

- Generates a visible and and accoustic signal a the same time
- Very good signaling effect
- Built-in drive circuit
- Extended operating voltage range
- Solder lug terminals

Technical Specifications

Operating Temperature Range: -20...+70°C

Material

Housing: Plastic

Pins:

Tin plated brass

Part No.	LED Colour	Tone/Pulse Rate
PK-27A35GQ	Green	Constant
PK-27A35RQ	Red	Constant
PK-27A35YQ	Yellow	Constant
PL-27A30GQ	Green	Slow Pulse 1,2 ¹⁾
PL-27A30RQ	Red	Slow Pulse 1,2 ¹⁾
PL-27A30YQ	Yellow	Slow Pulse 1,2 ¹⁾
PF-27A35GQ	Green	Fast Pulse 3,0
PF-27A35RQ	Red	Fast Pulse 3,0
PF-27A35YQ	Yellow	Fast Pulse 3,0

¹⁾ ±20% @U_N

Part No.	F _o [kHz]	U _R [V DC]	U _o [V DC]	I _c [mA]	SPL _{min} [dB]
PK-27A35GQ	3,5	12	3...15	18	95 ²⁾
PK-27A35RQ	3,5	12	3...15	18	95 ²⁾
PK-27A35YQ	3,5	12	3...15	18	95 ²⁾
PL-27A30GQ	3	12	3...15	25	95 ¹⁾
PL-27A30RQ	3	12	3...15	25	95 ¹⁾
PL-27A30YQ	3	12	3...15	25	95 ¹⁾
PF-27A35GQ	3,5	12	3...15	18	95 ¹⁾
PF-27A35RQ	3,5	12	3...15	18	95 ¹⁾
PF-27A35YQ	3,5	12	3...15	18	95 ¹⁾

F_o = Oscillation Frequency ($\pm 0,5$), U_R = Rated Voltage, U_o = Operation Voltage Range, I_c = Current Consumption, max. (@ U_R), SPL_{min} = Sound Pressure Level, min. (¹at 30cm @ U_R , ²at 10cm @ U_R)

Labelling



Productinformatie

Artikelnummer	PK27A35YQ
Merk	HITPOINT

