

**NETFILTER RFI IEC 2A 230V SCHAKELAAR EN ZEKERING FASTON 6.3MM
SCHROEFMONTAGE HORIZONTAAL**

€ 37,95

Excl. BTW: € 31,36

Afbeeldingen



Beschrijving

Features

- Filter built in a metal housing with integrated power line connector, fuse holder and 2-pole, non-illuminated line switch
- Fuse holder for two fuses 5x20mm
- For PCB mounting and faston plug terminal 6,3x0,8mm added
- **FN282_**, **FN284_**: Screw mounting from front or rear side
- **FN286_**: Snap-in mounting

Technical Specifications

Continuous Operating Voltage, Max.:

250V, 50/60Hz

Dielectric Strength, 2s

| | |
|------------------------------|-----------------|
| Line To Ground: | 2kV AC |
| Line To Ground B-Type: | 2,5kV AC |
| Line To Line: | 0,76kV AC |
| Temperature Range: | -25...+85°C |
| Protection Class Front Side: | IP40 |
| Ratings Rocker Switch: | 10 (4)A/250V AC |
| Inrush Current: | 82A |

| Part Nr. | I_R [A] | L [mH] | C_x [nF] | C_Y [nF] | I_L [μA] |
|-----------|--------------|-----------|---------------|---------------|---------------|
| FN282-2F | 2 | 2 | 220 | 2,2 | 373 |
| FN282-4F | 4 | 1 | 220 | 2,2 | 373 |
| FN282-6F | 6 | 0,45 | 220 | 2,2 | 373 |
| FN282-10F | 10 | 0,34 | 220 | 2,2 | 373 |
| FN284-1F | 1 | 7,5 | 220 | 2,2 | 373 |
| FN284-2F | 2 | 2 | 220 | 2,2 | 373 |
| FN284-4F | 4 | 1 | 220 | 2,2 | 373 |
| FN284-6F | 6 | 0,45 | 220 | 2,2 | 373 |
| FN284-10F | 10 | 0,34 | 220 | 2,2 | 373 |
| FN286-1F | 1 | 7,5 | 220 | 2,2 | 373 |
| FN286-2F | 2 | 2 | 220 | 2,2 | 373 |
| FN286-4F | 4 | 1 | 220 | 2,2 | 373 |
| FN286-6F | 6 | 0,45 | 220 | 2,2 | 373 |
| FN286-10F | 10 | 0,34 | 220 | 2,2 | 373 |

I_R = Rated Current, at 40°C, L = Inductance, I_L = Leakage Current, Max. at 230V, 50Hz

Approvals

Productinformatie

| | |
|---------------|-----------|
| Artikelnummer | FN284-2F |
| Merk | SCHAFFNER |

