

**NETFILTER RFI IEC 6A 230V SCHAKELAAR EN ZEKERING FASTON 6.3MM  
SCHROEFMONTAGE HORIZONTAAL**

**€ 39,95**

Excl. BTW: € 33,02

**Afbeeldingen**



**Beschrijving**

**Features**

- Filter built in a metal housing with integrated power line connector, fuse holder and 2-pole, non-illuminated line switch
- Fuse holder for two fuses 5x20mm
- For PCB mounting and faston plug terminal 6,3x0,8mm added
- **FN282\_**, **FN284\_**: Screw mounting from front or rear side
- **FN286\_**: Snap-in mounting

**Technical Specifications**

Continuous Operating Voltage, Max.:

250V, 50/60Hz

Dielectric Strength, 2s

Line To Ground:	2kV AC
Line To Ground B-Type:	2,5kV AC
Line To Line:	0,76kV AC
Temperature Range:	-25...+85°C
Protection Class Front Side:	IP40
Ratings Rocker Switch:	10 (4)A/250V AC
Inrush Current:	82A

Part Nr.	$I_R$ [A]	L [mH]	$C_x$ [nF]	$C_Y$ [nF]	$I_L$ [μA]
FN282-2F	2	2	220	2,2	373
FN282-4F	4	1	220	2,2	373
FN282-6F	6	0,45	220	2,2	373
FN282-10F	10	0,34	220	2,2	373
FN284-1F	1	7,5	220	2,2	373
FN284-2F	2	2	220	2,2	373
FN284-4F	4	1	220	2,2	373
FN284-6F	6	0,45	220	2,2	373
FN284-10F	10	0,34	220	2,2	373
FN286-1F	1	7,5	220	2,2	373
FN286-2F	2	2	220	2,2	373
FN286-4F	4	1	220	2,2	373
FN286-6F	6	0,45	220	2,2	373
FN286-10F	10	0,34	220	2,2	373

$I_R$  = Rated Current, at 40°C, L = Inductance,  $I_L$  = Leakage Current, Max. at 230V, 50Hz

## Approvals

## Productinformatie

---

Artikelnummer	FN284-6F
Merk	SCHAFFNER

