

**NETFILTER RFI IEC 4A 230V SCHAKELAAR EN ZEKERING FASTON 6.3MM
SNAPIN MONTAGE**

€ 37,95

Excl. BTW: € 31,36

Afbeeldingen



Beschrijving

Features

- Filter built in a metal housing with integrated power line connector, fuse holder and 2-pole, non-illuminated line switch
- Fuse holder for two fuses 5x20mm
- For PCB mounting and faston plug terminal 6,3x0,8mm added
- **FN282_**, **FN284_**: Screw mounting from front or rear side
- **FN286_**: Snap-in mounting

Technical Specifications

Continuous Operating Voltage, Max.:	250V, 50/60Hz
Dielectric Strength, 2s	
Line To Ground:	2kV AC
Line To Ground B-Type:	2,5kV AC
Line To Line:	0,76kV AC
Temperature Range:	-25...+85°C
Protection Class Front Side:	IP40
Ratings Rocker Switch:	10 (4)A/250V AC
Inrush Current:	82A

Part Nr.	I_R [A]	L [mH]	C_x [nF]	C_Y [nF]	I_L [μA]
FN282-2F	2	2	220	2,2	373
FN282-4F	4	1	220	2,2	373
FN282-6F	6	0,45	220	2,2	373
FN282-10F	10	0,34	220	2,2	373
FN284-1F	1	7,5	220	2,2	373
FN284-2F	2	2	220	2,2	373
FN284-4F	4	1	220	2,2	373
FN284-6F	6	0,45	220	2,2	373

FN284-10F	10	0,34	220	2,2	373
FN286-1F	1	7,5	220	2,2	373
FN286-2F	2	2	220	2,2	373
FN286-4F	4	1	220	2,2	373
FN286-6F	6	0,45	220	2,2	373
FN286-10F	10	0,34	220	2,2	373

I_R = Rated Current, at 40°C, L = Inductance, I_L = Leakage Current, Max. at 230V, 50Hz

Approvals



Productinformatie

Artikelnummer	FN286-4F
Merk	SCHAFFNER

