

**EMI NETFILTER 1 FASE 2 TRAPS 250V 12A MET 6,3MM FASTON AANSLUITING**

**€ 49,50**

Excl. BTW: € 40,91

**Afbeeldingen**



**Beschrijving**

**Features**

- Single phase filters, two-stage, built in a metal housing
- Compact design
- Universal application
- **FN2090F** Faston plug terminal 6,3x0,8mm
- **FN2090M**: Studs (M4 screws)

**Technical Specifications**

Continuous Operating Voltage, Max.:

250V AC, 50/60Hz; 250V DC

Dielectric Strength, 2s	
Line To Ground:	2kV AC
Line To Ground:	2,55kV DC
Line To Ground B-Type:	2,5kV AC
Line To Neutral:	1,1kV DC
Temperature Range:	-25...+100°C

Part Nr.	$I_R$	L	$C_X$	$C_{Y1}$	$C_{Y2}$	$I_L$
	[A]	[mH]	[ $\mu$ F]	[nF]	[nF]	[mA]
FN2090-1F	1	20	0,22	2,2	1,0	0,45
FN2090-3F	3	14	0,33	2,2	1,0	0,45
FN2090-4F	4	14	0,33	2,2	1,0	0,45
FN2090-6F	6	8	0,47	3,3	1,0	0,61
FN2090-8F	8	8	0,47	3,3	1,0	0,61
FN2090-10F	10	8	0,47	3,3	1,0	0,61
FN2090-12F	12	4	1	10	1,0	0,93
FN2090-16F	16	4	1	10	1,0	0,93
FN2090-20F	20	2,7	1	10	1,0	0,93
FN2090-20M	20	2,7	1	10	1,0	0,93
FN2090-30M	30	1,5	1	10	1,0	0,93

$I_R$  = Rated Current, at 40°C, L = Inductance,  $I_L$  = Leakage Current, Max. at 250V AC, 50Hz

## Productinformatie

Artikelnummer	FN2090-12F
Merk	SCHAFFNER

