

## GESCHAKELDE VOEDING SINGLE OUTPUT 321W 15V/21.4A

€ 69,95

Excl. BTW: € 57,81

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile



## Technical Specifications



Input Voltage:	88...264V AC (47...63Hz)
	124...370V DC
Input Inrush Current, Max.:	40A
Leakage Current, Max.:	1mA
Output Voltage Adjustment:	±10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	900g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	$U_A$	$I_A$	$P_A$	$U_{RN}$	h
	[V]	[A]	[W]	[mV <sub>p-p</sub> ]	[%]
RSP3202.5	2.5	0...60	150	100	75,5
RSP3203.3	3.3	0...60	198	100	79,5
RSP3204	4	0...60	240	100	81
RSP3205	5	0...60	240	150	83
RSP3207.5	7.5	0...40	300	150	88
RSP32012	12	0...26,7	320,4	150	88
RSP32013.5	13,5	0...23,8	321,3	150	88

RSP32015	15	0...21,4	321	150	88,5
RSP32024	24	0...13,4	321,6	150	89
RSP32027	27	0...11,9	321,3	200	89
RSP32036	36	0...8,9	320,4	220	89,5
RSP32048	48	0...6,7	321,6	240	90

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Productinformatie

Artikelnummer	RSP32015
Merk	MEANWELL

