

## GESCHAKELDE VOEDING SINGLE OUTPUT 321W 48V/6.7A

**€ 69,95**

Excl. BTW: € 57,81

## Afbeeldingen



## Beschrijving

## Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile



## Technical Specifications



|                             |                          |
|-----------------------------|--------------------------|
| Input Voltage:              | 88...264V AC (47...63Hz) |
|                             | 124...370V DC            |
| Input Inrush Current, Max.: | 40A                      |
| Leakage Current, Max.:      | 1mA                      |
| Output Voltage Adjustment:  | ±10%                     |
| Over Load Protection:       | 105...135%               |
| Withstand Voltage           |                          |
| I/P-O/P:                    | 3000V AC                 |
| I/P-FG:                     | 2000V AC                 |
| O/P-FG:                     | 500V AC                  |
| Operating Temperature:      | -30...+70°C              |
| Weight:                     | 900g                     |

I/P = Input, O/P = Output, FG = Frame Ground



| Part Nr.   | $U_A$ | $I_A$    | $P_A$ | $U_{RN}$             | $h$  |
|------------|-------|----------|-------|----------------------|------|
|            | [V]   | [A]      | [W]   | [mV <sub>p-p</sub> ] | [%]  |
| RSP3202.5  | 2.5   | 0...60   | 150   | 100                  | 75,5 |
| RSP3203.3  | 3.3   | 0...60   | 198   | 100                  | 79,5 |
| RSP3204    | 4     | 0...60   | 240   | 100                  | 81   |
| RSP3205    | 5     | 0...60   | 240   | 150                  | 83   |
| RSP3207.5  | 7.5   | 0...40   | 300   | 150                  | 88   |
| RSP32012   | 12    | 0...26,7 | 320,4 | 150                  | 88   |
| RSP32013.5 | 13,5  | 0...23,8 | 321,3 | 150                  | 88   |

|          |    |          |       |     |      |
|----------|----|----------|-------|-----|------|
| RSP32015 | 15 | 0...21,4 | 321   | 150 | 88,5 |
| RSP32024 | 24 | 0...13,4 | 321,6 | 150 | 89   |
| RSP32027 | 27 | 0...11,9 | 321,3 | 200 | 89   |
| RSP32036 | 36 | 0...8,9  | 320,4 | 220 | 89,5 |
| RSP32048 | 48 | 0...6,7  | 321,6 | 240 | 90   |

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

### Productinformatie

|               |          |
|---------------|----------|
| Artikelnummer | RSP32048 |
| Merk          | MEANWELL |
| Is on Sale    | Nee      |

