

STEKKER MALE 5P SOLDEER IP67

€ 26,95

Excl. BTW: € 22,27

Afbeeldingen



Beschrijving

Features

- Cable connector with screw locking according to IEC60130-9
- Internal strain relief
- Precision metal construction
- excellent EMC shielding
- Degree of protection IP67



Technical Specifications



Connector Locking System:	Screw
Termination:	Solder
Wire Gauge, Max.:	0,25mm ²

Cable Outlet, Max.:	4...6mm
Degree of Protection:	IP67
Mechanical Operating Life:	>500 Cycles
Temperature Range:	-30...+95°C
Rated Voltage:	see Table
Rated Current (40°C):	see Table
Contact Resistance, Max.:	see Table
Material of Contact:	CuZn
Material of Housing:	CuZn, Nickel-plated



Part-Nr.	Pole	U _N [V]	I _N [A]	R [mOhm]	Contact Plating
M16ML03	3	250 (32)	7	5	Ag
M16ML05	5	250 (32)	6	5	Ag
M16ML08	8	60 (32)	5	5	Ag
M16ML12	12	60 (32)	3	3	Au
M16FM03	3	250 (32)	7	5	Ag
M16FM05	5	250 (32)	6	5	Ag
M16FM08	8	60 (32)	5	5	Ag

U_N = Rated Voltage, I_N = Rated Current (40°C), R = Contact Resistance, Max

Productinformatie

Artikelnummer	M16ML05
Merk	BINDER

