

STEKKER MALE 5P SOLDEER IP67

€ 22,51

Excl. BTW: € 18,60

Afbeeldingen



Beschrijving

Features

--

--

--

• Cable connectors with screw locking
• Thread locking M12x1
• Screw connection
• Shield connection with shield ring/iris type spring
• UL versions
• Degree of protection IP67

--

--


--

--

--

--

--

--

--

Technical Specifications

--

--

--

--

```

<tbody>
<tr>
<td></td>
</tr>
<tr>
<td width="50%">&nbsp;</td>
<td width="50%">&nbsp;</td>
</tr>
<tr bgcolor="#dee7ef">
<td colspan="1" align="left" valign="top">Connector Locking System:</td>
<td colspan="1" align="right" valign="top">Screw</td>
</tr>
<tr bgcolor="#f4f8fc">
<td colspan="1" align="left" valign="top">Termination:</td>
<td colspan="1" align="right" valign="top">Screw</td>
</tr>
<tr bgcolor="#dee7ef">
<td colspan="1" align="left" valign="top">Wire Gauge, Max.:</td>
<td colspan="1" align="right" valign="top">0,75mm<span><sup>2</sup></span></td>
</tr>
<tr bgcolor="#f4f8fc">
<td colspan="1" align="left" valign="top">Cable Outlet, Max.:</td>
<td colspan="1" align="right" valign="top">4...6mm</td>
</tr>
<tr bgcolor="#dee7ef">
<td colspan="1" align="left" valign="top">Degree of Protection:</td>
<td colspan="1" align="right" valign="top">IP67</td>
</tr>
<tr bgcolor="#f4f8fc">
<td colspan="1" align="left" valign="top">Mechanical Operating Life:</td>
<td colspan="1" align="right" valign="top">&gt;50 Cycles</td>
</tr>
<tr bgcolor="#dee7ef">
<td colspan="1" align="left" valign="top">Temperature Range:</td>
<td colspan="1" align="right" valign="top">-25...+85&deg;C</td>
</tr>
<tr bgcolor="#f4f8fc">
<td colspan="2" align="left" valign="top">Rated Voltage</td>
</tr>
<tr bgcolor="#dee7ef">
<td colspan="1" align="left" valign="top">M12MLO4:</td>
<td colspan="1" align="right" valign="top">250V</td>
</tr>
<tr bgcolor="#f4f8fc">
<td colspan="1" align="left" valign="top">M12MLO5</td>
<td colspan="1" align="right" valign="top">125V</td>
</tr>
<tr bgcolor="#dee7ef">
<td colspan="1" align="left" valign="top">Rated Current (40&deg;C):</td>
<td colspan="1" align="right" valign="top">4A</td>
</tr>
<tr bgcolor="#f4f8fc">
<td colspan="1" align="left" valign="top">Contact Resistance, Max.:</td>
<td colspan="1" align="right" valign="top">8mOhm</td>

```

```

</tr>
<tr bgcolor="#dee7ef">
<td colspan="1" align="left" valign="top">Material of Contact:</td>
<td colspan="1" align="right" valign="top">CuZn, Optaloy</td>
</tr>
<tr bgcolor="#f4f8fc">
<td colspan="1" align="left" valign="top">Material of Housing:</td>
<td colspan="1" align="right" valign="top">PA</td>
</tr>
</tbody>
</table>

```

Productinformatie

Artikelnummer	M12MLO5
Merk	BINDER

