

## LED DRIVER 350MA 9-36V 12W IP42

€ 8,95

Excl. BTW: € 7,40

### Afbeeldingen



### Beschrijving

#### Features

- Universal input
- Plastic enclosure IP42
- Protections: short circuit, over voltage
- Suitable for LED lighting and moving sign applications
- Constant current

## Technical Specifications

Input Voltage:	180...264V AC (47...63Hz)
	254...370V DC
Input Inrush Current, Max.:	70A
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-30...+70°C
Weight:	80g

I/P = Input, O/P = Output

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[mA]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
APC12E350	9...36	350	12,6	5	300	81
APC12E700	9...18	700	12,6	5	250	79

$U_A$  = Output Voltage Range,  $I_A$  = Output Current,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Typ. Efficiency

### Note

Devices only for use in equipment with another primary purpose such as photocopiers, overhead projectors and slide projectors or for scale illumination or indication purposes.

Suitable for indoor use.

## Productinformatie

Artikelnummer	APC12E350
Merk	MEANWELL

