

LED DRIVER 700MA 9-18V 12W IP42

€ 8,95

Excl. BTW: € 7,40

Afbeeldingen



Beschrijving

Features

- Universal input
- Plastic enclosure IP42
- Protections: short circuit, over voltage
- Suitable for LED lighting and moving sign applications
- Constant current

Technical Specifications

Input Voltage:	180...264V AC (47...63Hz)
	254...370V DC
Input Inrush Current, Max.:	70A
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-30...+70°C
Weight:	80g

I/P = Input, O/P = Output

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[mA]	[W]	[%]	[mV _{p-p}]	[%]
APC-12E-350	9...36	350	12,6	5	300	81
APC-12E-700	9...18	700	12,6	5	250	79

U_A = Output Voltage Range, I_A = Output Current, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Typ. Efficiency

Note

Devices only for use in equipment with another primary purpose such as photocopiers, overhead projectors and slide projectors or for scale illumination or indication purposes.

Suitable for indoor use.

Productinformatie

Artikelnummer	APC12E700
Merk	MEANWELL

