


LED VOEDING 15V/1.00A 15W IP30 BEHUIZING

€ 12,50

Excl. BTW: € 10,33

Afbeeldingen



Beschrijving

Features

- Independent power supply
- Universal input
- Plastic enclosure IP42
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Suitable for LED lighting and moving sign applications
- Constant voltage



Technical Specifications



Input Voltage:

90...264V AC (47...63Hz)

127...370V DC

Input Inrush Current, Max.:	50A
Over Current Protection:	105 %
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-30...+70°C
Weight:	100g

I/P = Input, O/P = Output



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
APV1605	5	0...2,6	13	5	100	76
APV1612	12	0...1,25	15	5	120	80
APV1615	15	0...1	15	5	120	81
APV1624	24	0...0,67	16,08	5	150	83

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{RN} = Ripple & Noise, h = Typ. Efficiency

Productinformatie

Artikelnummer	APV1615
Merk	MEANWELL

