

ACCU 12V 100A 407X172X240MM 39.0KG AANSLUITING M10

€ 479,00

Excl. BTW: € 395,87

Afbeeldingen



Beschrijving

Features

- Electrolyte bound in the glass fiber fleece
- Lead-calcium grids for a longer service life
- Valve controlled construction, almost 100% oxygen recombination
- Very good charging efficiency
- Fast recovery after deep discharge

Technical Specifications

Nominal Voltage:	12V
Housing Material:	ABS

Low self-discharge, at 20 ° C:	3% per month
Storage (in fully charged condition)	
NPL24-12I, NPL38-12I:	-20...+60°C
NPL65-12I, NPL100-12:	-20...+50°C
EUROBAT Classification (Standard Commercial):	10 to 12 years

Part No.	C _N [Ah]	L [mm]	W [mm]	H _T [mm]	Weight [kg]	Terminal Type
NPL24-12I	24	166	175	125	9,8	M5 (F)
NPL38-12I	38	197	165	170	13,7	M5 (F)
NPL65-12I	65	350	166	174	22,6	M6 (F)
NPL100-12	100	407	172	240	39	M10 LUG

C_N = 20-hr rate Capacity to 10.5V at 20°C, L = Length (Tolerances see data sheet),
W = Width (Tolerances see data sheet), H_T = Total Height (Tolerances see data sheet)

Recycling

All used lead batteries must be given to an environmentally-friendly waste bank for disposal in accordance with local regulations.

Do not dispose of used batteries in domestic waste!

Productinformatie

Artikelnummer	NPL100-12I
Merk	YUASA

