

**ACCU 12V 38A 197X165X170MM 13.6KG AANSLUITING M5**

**€ 185,00**

Excl. BTW: € 152,89

**Afbeeldingen**



**Beschrijving**

**Features**

- Electrolyte bound in the glass fiber fleece
- Lead-calcium grids for a longer service life
- Valve controlled construction, almost 100% oxygen recombination
- Very good charging efficiency
- Fast recovery after deep discharge

**Technical Specifications**

Nominal Voltage:	12V
Housing Material:	ABS

Low self-discharge, at 20 ° C:	3% per month
Storage (in fully charged condition)	
<b>NPL24-12I, NPL38-12I:</b>	-20...+60°C
<b>NPL65-12I, NPL100-12:</b>	-20...+50°C
EUROBAT Classification (Standard Commercial):	10 to 12 years

Part No.	C <sub>N</sub> [Ah]	L [mm]	W [mm]	H <sub>T</sub> [mm]	Weight [kg]	Terminal Type
<b>NPL24-12I</b>	24	166	175	125	9,8	M5 (F)
<b>NPL38-12I</b>	38	197	165	170	13,7	M5 (F)
<b>NPL65-12I</b>	65	350	166	174	22,6	M6 (F)
<b>NPL100-12</b>	100	407	172	240	39	M10 LUG

C<sub>N</sub> = 20-hr rate Capacity to 10.5V at 20°C, L = Length (Tolerances see data sheet),  
W = Width (Tolerances see data sheet), H<sub>T</sub> = Total Height (Tolerances see data sheet)

### Recycling

All used lead batteries must be given to an environmentally-friendly waste bank for disposal in accordance with local regulations.

Do not dispose of used batteries in domestic waste!

### Productinformatie

Artikelnummer	NPL38-12I
Merk	YUASA

