

ACCU 12V 7.5A 151X65X98MM 2.6KG AANSLUITING FASTON 6.3MM

€ 37,50

Excl. BTW: € 30,99

Afbeeldingen



Beschrijving

Features

- Electrolyte bound in the glass fiber fleece
- Lead-calcium grids for a longer service life
- Valve controlled construction, almost 100% oxygen recombination
- Very good charging efficiency
- Fast recovery after deep discharge
- High rate discharge performance VRLA battery

Technical Specifications

| | |
|--|----------------|
| Nominal Voltage: | 12V |
| Housing Material: | ABS |
| Low self-discharge, at 20 ° C: | 3% per month |
| EUROBAT Classification (Standard Commercial) | |
| Series SW : | 6 to 9 years |
| Series SWL : | 10 to 12 years |

| Part No. | P | T _s |
|----------|------|----------------|
| | [W] | [°C] |
| SW280 | 280 | -20...+60 |
| SWL780V | 780 | -20...+60 |
| SWL1100 | 1100 | -20...+60 |
| SWL1850 | 1850 | -20...+50 |
| SWL3300 | 3300 | -20...+50 |

P = 10m rate Constant Power (Typ) to 9,6V at 20°C (W/Block), T_s = Storage (in fully charged condition)

Terminal Type, Dimensions and Weight

| Part No. | Terminal Type | L | W | H | Weight |
|----------|---------------|------|------|------|--------|
| | | [mm] | [mm] | [mm] | [kg] |
| SW280 | Faston 6,35 | 151 | 65 | 97,5 | 2,6 |
| SWL1100 | M5 (F) | 166 | 125 | 175 | 10,3 |
| SWL1850 | M6 (F) | 197 | 165 | 170 | 14,5 |
| SWL3300 | M8 (F) | 350 | 166 | 174 | 23,3 |
| SWL780V | M5 (F) | 350 | 168 | 225 | 37,7 |

L = Length (Tolerances see data sheet), W = Width (Tolerances see data sheet),
H = Total Height (Tolerances see data sheet)

Recycling

All used lead batteries must be given to an environmentally-friendly waste bank for disposal in accordance with local regulations.

Do not dispose of used batteries in domestic waste!

Productinformatie

| | |
|---------------|-------|
| Artikelnummer | SW280 |
| Merk | YUASA |

