

ACCU 12V 7.0A 151X65X94MM 2250GR AANSLUITING FASTON 6.3MM

€ 34,50

Excl. BTW: € 28,51

Afbeeldingen



Beschrijving

Features

- Powerful and maintenance-free lead-acid battery
- Absorbent glass mat technology
- Sealed, leak-resistant ABS container

Technical Specifications

Part No.

U_N

C_N

Designed floating life

[V]

[Ah]

[Years]

XPO.8-12AMP	12	0,8	10
XP1.2-12	12	1,2	3...5
XP2.3-12	12	2,3	3...5
XP3.4-12	12	3,4	-
XP7-12	12	7,08	5
XP12-12F2	12	12	3...5
XP18-12	12	18	3...5
XP26-12	12	26	3...5
XP45-12	12	45	12
XP65-12	12	65	7...10

U_N = Nominal Voltage, C_N = Nominal Capacity (@ 25°C)

Dimensions, Weight and Connection

Part No.	L x W x H [mm]	H _T [mm]	Weight [g]	Connection [mm]
XPO.8-12AMP	96x25x62	62	330	Plug AMP
XP1.2-12	97x43x52	58	540	Flat Plug 4,8
XP2.3-12	178x35x61	67	900	Flat Plug 4,8
XP3.4-12	134x67x60,5	66,5	1200	Flat Plug 4,75
XP7-12	151x65x94	100	2250	Flat Plug 4,8/6,4
XP12-12F2	151x98x95	101	3600	Flat Plug 6,35/4,8
XP18-12	181x77x167	167	5300	Srew Terminal Ø5,5/M5
XP26-12	165x176x127	127	7900	Srew Terminal Ø5,5/M5
XP45-12	197x165x170	170	14000	Srew Terminal Ø6/M6
XP65-12	350x167x179	186	20800	Srew Terminal Ø8/M6

H_T = Total Height

Recycling

All used lead batteries must be given to an environmentally-friendly waste bank for disposal in accordance with local regulations.

Do not dispose of used batteries in domestic waste!

Productinformatie

Artikelnummer	XP7-12
Merk	XCELL

