

ACCU 12V 41A 166X125X175MM 10.3KG AANSLUITING M5

€ 139,00

Excl. BTW: € 114,88

## Afbeeldingen



## Beschrijving

### Features

- Electrolyte bound in the glass fiber fleece
- Lead-calcium grids for a longer service life
- Valve controlled construction, almost 100% oxygen recombination
- Very good charging efficiency
- Fast recovery after deep discharge
- High rate discharge performance VRLA battery

### Technical Specifications

Nominal Voltage:	12V
Housing Material:	ABS
Low self-discharge, at 20 ° C:	3% per month
EUROBAT Classification (Standard Commercial)	
Series <b>SW</b> :	6 to 9 years
Series <b>SWL</b> :	10 to 12 years

Part No.	P	T <sub>s</sub>
	[W]	[°C]
SW280	280	-20...+60
SWL780V	780	-20...+60
SWL1100	1100	-20...+60
SWL1850	1850	-20...+50
SWL3300	3300	-20...+50

P = 10m rate Constant Power (Typ) to 9,6V at 20°C (W/Block), T<sub>s</sub> = Storage (in fully charged condition)

### Terminal Type, Dimensions and Weight

Part No.	Terminal Type	L	W	H	Weight
		[mm]	[mm]	[mm]	[kg]
SW280	Faston 6,35	151	65	97,5	2,6
SWL1100	M5 (F)	166	125	175	10,3
SWL1850	M6 (F)	197	165	170	14,5
SWL3300	M8 (F)	350	166	174	23,3
SWL780V	M5 (F)	350	168	225	37,7

L = Length (Tolerances see data sheet), W = Width (Tolerances see data sheet),  
H = Total Height (Tolerances see data sheet)

### Recycling

All used lead batteries must be given to an environmentally-friendly waste bank for disposal in accordance with local regulations.

Do not dispose of used batteries in domestic waste!

### Productinformatie

---

Artikelnummer	SWL1100
Merk	YUASA

