

ACCU 12V 7.0A 151X65X97,5MM 2650GR AANSLUITING 6,3MM

€ 37,99

Excl. BTW: € 31,40

Afbeeldingen



Beschrijving

Features

- Electrolyte bound in the glass fiber fleece
- Lead-calcium grids for a longer service life
- Valve controlled construction, almost 100% oxygen recombination
- Very good charging efficiency
- Fast recovery after deep discharge

Technical Specifications

Nominal Voltage:	12V
Housing Material:	ABS

Low self-discharge, at 20 ° C:	3% per month
Storage (in fully charged condition):	-20...+60°C
EUROBAT Classification (Standard Commercial):	3 to 5 years

Part No.	C _N [Ah]	L [mm]	W [mm]	H _T [mm]	Weight [kg]	Terminal Type
NP1.2-12	1,2	97	48	54,5	0,58	Faston 4,75
NP2.3-12	2,3	178	34	64	0,95	Faston 4,75
NP3.2-12	3,2	134	67	64	1,1	Faston 4,75
NP4-12	4	90	70	106	1,75	Faston 4,75
NP7-12	7	151	65	97,5	2,2	Faston 4,75
NP7-12L	7	151	65	97,5	2,2	Faston 6,35
NP12-12	12	151	98	97,5	4,05	Faston 6,35
NP17-12	17	181	76	167	6,1	M5 (F)
NP18-12B	17,2	180	76	167	6,2	M5 LUG
NP24-12	24	166	175	125	9	M5 (F)
NP38-12	38	197	165	170	14,2	M5 (F)
NP65-12	65	350	166	174	23	M6 (F)

C_N = 20-hr rate Capacity to 10.5V at 20°C, L = Length (Tolerances see data sheet),
W = Width (Tolerances see data sheet), H_T = Total Height (Tolerances see data sheet)

Recycling

All used lead batteries must be given to an environmentally-friendly waste bank for disposal in accordance with local regulations.

Do not dispose of used batteries in domestic waste!

Productinformatie

Artikelnummer	WP7-12YL
Merk	YUASA

