

RELAIS 1 X MAAK 12VDC 5A 720 OHM

€ 2,95

Excl. BTW: € 2,44

## Afbeeldingen



## Beschrijving

### Features

- Slim type with 7mm width
- High switching current
- High insulation: min. 6mm between coil and contact
- Cadmium free contacts
- Wash tight construction RTIII

## Technical Specifications

Contact:	SPST-NO
Contact Material	
FTRF3AA_HA:	AgNi
Rated Switching Current	
FTRF3AA_HA:	5A
Max. Switching Voltage	
FTRF3AA_HA:	277V AC / 30V DC
Max. Switching Power:	750VA / 90W
Creepage/Clearance	
FTRF3AA_HA:	6/6mm
Operate/Release Time:	10/10ms
Testing Voltage	
Coil/Contact (1min.):	4000V AC
Open Contact (1min.):	750V AC
Min. Lifetime	
Mechanical:	5x10 <sup>6</sup> Operations
Electrical	
FTRF3AA_HA:	200x10 <sup>3</sup> Operations
Operating Temperature	
FTRF3AA_HA:	-40...+70°C
Weight Approx.	
FTRF3AA_HA:	4g

## Productinformatie

---

Artikelnummer	R012D1MR
Merk	FUJITSU
Is on Sale	Nee

