

GESCHAKELDE VOEDING SINGLE OUTPUT 62W 12V/5.2A

€ 21,95

Excl. BTW: € 18,14

Afbeeldingen



Beschrijving

Features

- Compact case, 4" x 2"
- Contact pin for nylon-crimp terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low no load power consumption
- Safety standards: EN62368-1
- EMC standards: EN55032 Class B, EN61000-3-2
- 3 years manufacturer warranty
- **EPS-65_**: Open frame
- **EPS-65_-C**: Enclosed type

Technical Specifications

| | |
|-----------------------------|--------------------------|
| Input Voltage: | 90...264V AC (47...63Hz) |
| | 127...370V DC |
| Input Inrush Current, Max.: | 60A |
| Leakage Current, Max.: | 2mA |
| Over Load Protection: | 115...160% |
| Withstand Voltage | |
| I/P-O/P: | 3000V AC |
| I/P-FG: | 2000V AC |
| O/P-FG: | 500V AC |
| Operating Temperature: | -30...+70°C |
| Weight: | 150g |

I/P = Input, O/P = Output, FG = Frame Ground

| Part Nr. | U_A | I_A | P_A | DU_A | U_{RN} | h |
|--------------|-------|--------|-------|--------|----------------------|-----|
| | [V] | [A] | [W] | [%] | [mV _{p-p}] | [%] |
| EPS-65-3.3 | 3,3 | 0...12 | 36,3 | ±3 | 80 | 80 |
| EPS-65-3.3-C | 3,3 | 0...12 | 36,3 | ±3 | 80 | 80 |
| EPS-65-5 | 5 | 0...12 | 55 | ±2 | 80 | 82 |

| | | | | | | |
|--------------|-----|----------|-------|----|-----|----|
| EPS-65-5-C | 5 | 0...12 | 55 | ±2 | 80 | 82 |
| EPS-65-7.5 | 7,5 | 0...8,8 | 60 | ±2 | 100 | 84 |
| EPS-65-7.5-C | 7,5 | 0...8,8 | 60 | ±2 | 100 | 84 |
| EPS-65-12 | 12 | 0...6 | 65,04 | ±2 | 120 | 86 |
| EPS-65-12-C | 12 | 0...6 | 65,04 | ±2 | 120 | 86 |
| EPS-65-15 | 15 | 0...4,8 | 65,1 | ±2 | 150 | 87 |
| EPS-65-24 | 24 | 0...3 | 65,04 | ±1 | 240 | 88 |
| EPS-65-24-C | 24 | 0...3 | 65,04 | ±1 | 240 | 88 |
| EPS-65-36 | 36 | 0...2 | 65,16 | ±1 | 280 | 89 |
| EPS-65-36-C | 36 | 0...2 | 65,16 | ±1 | 280 | 89 |
| EPS-65-48 | 48 | 0...1,36 | 65,28 | ±1 | 300 | 90 |
| EPS-65-48-C | 48 | 0...1,36 | 65,28 | ±1 | 300 | 90 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | EPS6512 |
| Merk | MEANWELL |

