

GESCHAKELDE VOEDING SINGLE OUTPUT 62W 13.5V/4.7A

€ 21,95

Excl. BTW: € 18,14

Afbeeldingen



Beschrijving

**Features**

- Compact case, 4" x 2"
- Contact pin for nylon-crimp terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low no load power consumption
- Safety standards: EN62368-1
- EMC standards: EN55032 Class B, EN61000-3-2
- 3 years manufacturer warranty
- **EPS-65\_**: Open frame
- **EPS-65\_-C**: Enclosed type

**Technical Specifications**

Input Voltage:	90...264V AC (47...63Hz) 127...370V DC
Input Inrush Current, Max.:	60A
Leakage Current, Max.:	2mA
Over Load Protection:	115...160%

Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	150g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	$U_A$ [V]	$I_A$ [A]	$P_A$ [W]	$DU_A$ [%]	$U_{RN}$ [mV <sub>p-p</sub> ]	h [%]
EPS-65-3.3	3,3	0...12	36,3	±3	80	80
EPS-65-3.3-C	3,3	0...12	36,3	±3	80	80
EPS-65-5	5	0...12	55	±2	80	82
EPS-65-5-C	5	0...12	55	±2	80	82
EPS-65-7.5	7,5	0...8,8	60	±2	100	84
EPS-65-7.5-C	7,5	0...8,8	60	±2	100	84
EPS-65-12	12	0...6	65,04	±2	120	86
EPS-65-12-C	12	0...6	65,04	±2	120	86
EPS-65-15	15	0...4,8	65,1	±2	150	87
EPS-65-24	24	0...3	65,04	±1	240	88
EPS-65-24-C	24	0...3	65,04	±1	240	88
EPS-65-36	36	0...2	65,16	±1	280	89
EPS-65-36-C	36	0...2	65,16	±1	280	89
EPS-65-48	48	0...1,36	65,28	±1	300	90
EPS-65-48-C	48	0...1,36	65,28	±1	300	90

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

Artikelnummer EPS6513

Merk MEANWELL

