


## LED DRIVER 2-43VDC 250MA 10W 115X34X19MM

€ 17,94

Excl. BTW: € 14,83

### Afbeeldingen



FEATURES	
Rated Voltage	100 V 110...127 V 220...240 V
Constant Current ▾	
Dimming:	NOT DIMMABLE
Additional technical features:	RIPPLE FREE SELV <> WIDE RANGE INPUT VOLTAGE
Approvals:	ENEC EAC CE
Plastic case:	Square IP 20 (Independent Use)
Minimum cut-out hole diameter:	40 mm
Size:	115 x 19 x 34 mm
last update:	7/30/2021
Output voltage (min/max) ▾	

Model	Input Voltage (V)	Output Voltage (V)	Output Current (mA)	Power (W)	Efficiency (%)	Temp. Rise (°C)	Temp. Range (°C)	IP Rating	Mounting	Lead Time (days)
LED 115 100V-240V	100-240	12-18	250	10	85	40	-40 to +85	IP20	Surface Mount	14
LED 115 110V-127V	110-127	12-18	250	10	85	40	-40 to +85	IP20	Surface Mount	14
LED 115 220V-240V	220-240	12-18	250	10	85	40	-40 to +85	IP20	Surface Mount	14

### Beschrijving

#### Features

- Active Power Factor Corrector.
- IP20 independent driver, for indoor use.
- Class II protection against electric shock for direct or indirect contact.
- Supplied with terminal cover and cable retainer.
- Input and output terminal blocks on opposite sides (wire cross-section up to 2,5 mm<sup>2</sup> / AWG13).
- Single terminal block on primary and secondary circuit.
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm.
- Driver can be secured with slot for screws.
- Protections:
  - against overheating and short circuits;
  - against mains voltage spikes;

- against overloads.
- Thermal protection = C.5.a.

Productinformatie

Artikelnummer	127699
Merk	TCI
Is on Sale	Nee

