


LED DRIVER 2-24VDC 500MA 12W 115X34X19MM

€ 17,94

Excl. BTW: € 14,83

Afbeeldingen



FEATURES	
Rated Voltage	100 V 110...127 V 220...240 V
Constant Current ▾	
Dimming:	NOT DIMMABLE
Additional technical features:	RIPPLE FREE ACTIVE PFC (p>0.9) SELV 4s WIDE RANGE INPUT VOLTAGE
Approvals:	ENEC RCM CE EAC UKCA
Plastic case:	IP 20 (Independent Use)
Minimum cut-out hole diameter:	40 mm
Size:	115 x 19 x 34 mm
last update:	7/30/2021
Output voltage (min/max) ▾	
500 mA	2...24

Model	Output	Power	Temp	Temp	Temp	Temp	Temp	Temp	Temp
LED 12V 500mA	12V	12W	25°C	50°C	75°C	100°C	125°C	150°C	175°C
LED 18V 500mA	18V	18W	25°C	50°C	75°C	100°C	125°C	150°C	175°C
LED 24V 500mA	24V	24W	25°C	50°C	75°C	100°C	125°C	150°C	175°C

Beschrijving

Features

- Active Power Factor Corrector.
- IP20 independent driver, for indoor use.
- Class II protection against electric shock for direct or indirect contact.
- Supplied with terminal cover and cable retainer.
- Input and output terminal blocks on opposite sides (wire cross-section up to 2,5 mm² / AWG13).
- Single terminal block on primary and secondary circuit.
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm.
- Driver can be secured with slot for screws.
- Protections:
 - against overheating and short circuits;

- against mains voltage spikes;
- against overloads.
- Thermal protection = C.5.a.

Productinformatie

Artikelnummer	127711
Merk	TCI
Is on Sale	Nee

