


## LED DRIVER 2-24VDC 500MA 12W 115X34X19MM

€ 17,94

Excl. BTW: € 14,83

### Afbeeldingen



FEATURES	
Rated Voltage	100 V 110...127 V 220...240 V
Constant Current ▾	
Dimming:	NOT DIMMABLE
Additional technical features:	<ul style="list-style-type: none"> <li>✓ RIPPLE FREE</li> <li>✓ ACTIVE PFC (pF=0.9)</li> <li>✓ SELV 4+</li> <li>✓ WIDE RANGE INPUT VOLTAGE</li> </ul>
Approvals:	<ul style="list-style-type: none"> <li>✓ ENEC</li> <li>✓ RoHS</li> <li>✓ CE</li> <li>✓ EAC</li> <li>✓ UKCA</li> </ul>
Plastic case:	IP 20 (Independent Use)
Minimum cut-out hole diameter:	40 mm
Size:	115 x 19 x 34 mm
last update:	7/30/2021
Output voltage (min/max) ▾	
500 mA	2...24

Model	Input Voltage	Output Voltage	Output Current	Power	Efficiency	Temp. Rise	Temp. Range	Temp. Coefficient
LED 115 24V 500mA	100V-240V	24V	500mA	12W	85%	40°C	-40°C to +85°C	0.5%/°C
LED 115 12V 500mA	100V-240V	12V	500mA	12W	85%	40°C	-40°C to +85°C	0.5%/°C
LED 115 6V 500mA	100V-240V	6V	500mA	12W	85%	40°C	-40°C to +85°C	0.5%/°C
LED 115 3V 500mA	100V-240V	3V	500mA	12W	85%	40°C	-40°C to +85°C	0.5%/°C

### Beschrijving

#### Features

- Active Power Factor Corrector.
- IP20 independent driver, for indoor use.
- Class II protection against electric shock for direct or indirect contact.
- Supplied with terminal cover and cable retainer.
- Input and output terminal blocks on opposite sides (wire cross-section up to 2,5 mm<sup>2</sup> / AWG13).
- Single terminal block on primary and secondary circuit.
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm.
- Driver can be secured with slot for screws.
- Protections:
  - against overheating and short circuits;

- against mains voltage spikes;
- against overloads.
- Thermal protection = C.5.a.

Productinformatie

Artikelnummer	127711
Merk	TCI
Is on Sale	Nee

