


LED DRIVER 2-16VDC 700MA 12W 115X34X19MM

€ 17,94

Excl. BTW: € 14,83

Afbeeldingen



FEATURES	
Rated Voltage	100 V 110...127 V 220...240 V
Constant Current ▾	
Dimming:	NOT DIMMABLE
Additional technical features:	RIPPLE FREE ACTIVE PFC (pF=0.9) SELV < 60 V WIDE RANGE INPUT VOLTAGE
Approvals:	ENEC RCM CE EAC UKCA
Plastic case:	IP 20 (Independent Use)
Minimum cut-out hole diameter:	40 mm
Size:	115 x 19 x 34 mm
last update:	7/30/2021
Output voltage (min/max) ▾	

Model	Input Voltage (V)	Output Voltage (V)	Output Current (mA)	Power (W)	Efficiency (%)	Temp. Rise (°C)	Temp. Range (°C)	Temp. Coefficient (ppm/°C)	Temp. Stability (ppm/°C)	Temp. Drift (ppm/°C)	Temp. Hysteresis (ppm/°C)	Temp. Recovery (ppm/°C)	Temp. Settling (ppm/°C)	Temp. Drift (ppm/°C)	Temp. Hysteresis (ppm/°C)	Temp. Recovery (ppm/°C)	Temp. Settling (ppm/°C)
LED 12V 700mA	100-240	12.0	700	8.4	90	10	-40 to +85	100	10	10	10	10	10	10	10	10	10
LED 12V 700mA	100-240	12.0	700	8.4	90	10	-40 to +85	100	10	10	10	10	10	10	10	10	10
LED 12V 700mA	100-240	12.0	700	8.4	90	10	-40 to +85	100	10	10	10	10	10	10	10	10	10
LED 12V 700mA	100-240	12.0	700	8.4	90	10	-40 to +85	100	10	10	10	10	10	10	10	10	10

Beschrijving

Features

- Active Power Factor Corrector.
- IP20 independent driver, for indoor use.
- Class II protection against electric shock for direct or indirect contact.
- Supplied with terminal cover and cable retainer.
- Input and output terminal blocks on opposite sides (wire cross-section up to 2,5 mm² / AWG13).
- Single terminal block on primary and secondary circuit.
- Clamping screws on primary and secondary circuits for cables with diameter: min. 3 mm - max. 8 mm.
- Driver can be secured with slot for screws.
- Protections:
 - against overheating and short circuits;
 - against mains voltage spikes;

- against overloads.
- Thermal protection = C.5.a.

[Klik hier om de datasheet te bekijken](#)

Productinformatie

Artikelnummer	127712
Merk	TCI
Is on Sale	Nee

