


LED DRIVER 2-12VDC 500MA 6W

€ 17,94

Excl. BTW: € 14,83

Afbeeldingen



Beschrijving

Features

- Universal input
- Constant current
- Not dimmable
- Plastic housing IP20
- Low profile (11mm high)
- Overload protection by shutdown, auto recovery
- Protected against short circuit, overload
- For LED and lighting applications
- Safety standards: IEC 61347-1; IEC 61347-2-13; EN 61347-1; EN 61347-2-13
- EMC standards: EN 55015
- 3 years manufacturer warranty

Technical Specifications

Input Voltage:	198...264V AC (47...63Hz)
Input Inrush Current, Max.:	11A
Withstand Voltage (I/P-O/P):	3750V AC
Operating Temperature:	-20...+50°C
Dimensions(LxWxH):	98x46x11mm
Weight:	45g

I/P = Input, O/P = Output

Part Nr.	U_A	I_A	P_A	I_{RN}	h
	[V]	[mA]	[W]	[A _{p-p}]	[%]
RACD06-350-LP	2...18	350	6	0,05	77
RACD06-500-LP	2...12	500	6	0,05	75
RACD06-700-LP	2...9	700	6	0,05	74

U_A = Output Voltage, I_A = Output Current, P_A = Output Power, I_{RN} = Ripple & Noise, h = Typ. Efficiency

Productinformatie

Artikelnummer	RACD06-50L
Merk	RECOM

