


## LED DRIVER 10-21VDC 700MA 7W

€ 24,95

Excl. BTW: € 20,62

### Afbeeldingen



### Beschrijving

#### Features

- Universal input
- Constant current
- Not dimmable
- Plastic housing IP67
- Overload protection by current limiting
- Protected against short circuit, overload, overvoltage
- For LED and lighting applications
- Protection class II
- Safety standards: UL 8750; UL 1310; IEC 61347-2-13; IEC 61347-1; EN 61347-2-13; EN 61347-1
- EMC standards: EN 55015
- 3 years manufacturer warranty



#### Technical Specifications



|                              |                          |
|------------------------------|--------------------------|
| Input Voltage:               | 90...295V AC (47...63Hz) |
| Overload Protection:         | 105...120%               |
| No-load power, less than:    | 0,5W                     |
| Withstand Voltage (I/P-O/P): | 3750V AC                 |
| Operating Temperature:       | -20...+40°C              |
| Dimensions(LxWxH):           | 57x40.8x24mm             |
| Weight:                      | 74g                      |

I/P = Input, O/P = Output



| Part Nr.          | $U_A$   | $I_A$ | $P_A$ | $DI_A$ | $I_{RN}$ | $h$ |
|-------------------|---------|-------|-------|--------|----------|-----|
|                   | [V]     | [mA]  | [W]   | [%]    | [mA]     | [%] |
| <b>RACD07-350</b> | 21...10 | 350   | 7     | 3      | 30       | 70  |
| <b>RACD07-700</b> | 11...3  | 700   | 7     | 3      | 30       | 70  |

$U_A$  = Output Voltage,  $I_A$  = Output Current,  $P_A$  = Output Power,  $DI_A$  = Output Current Tolerance,  $I_{RN}$  = Ripple & Noise,  $h$  = Typ. Efficiency

## Productinformatie

|               |            |
|---------------|------------|
| Artikelnummer | RACD07-700 |
| Merk          | RECOM      |

