


GESCHAKELDE VOEDING SINGLE OUTPUT 750W 12V/62.5A

€ 259,00

Excl. BTW: € 214,05

Afbeeldingen



Beschrijving

Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Built-in remote On/Off control
- Built-in remote sense function
- DC OK signal
- Built-in auxiliary power 5V/0,5A
- Trimming function for output voltage and output current between 40...110% by 2...5,5VDC external voltage



Technical Specifications



| | |
|-----------------------------|--------------------------|
| Input Voltage: | 90...264V AC (47...63Hz) |
| | 127...370V DC |
| Input Inrush Current, Max.: | 40A |
| Leakage Current, Max.: | 2mA |
| Output Voltage Adjustment: | ±10% |
| Over Load Protection: | 105...125% |
| Withstand Voltage | |
| I/P-O/P: | 3000V AC |
| I/P-FG: | 2000V AC |
| O/P-FG: | 500V AC |
| Operating Temperature: | -30...+70°C |
| Weight: | 1640g |

I/P = Input, O/P = Output, FG = Frame Ground



| Part Nr. | U_A | I_A | P_A | DU_A | U_{RN} | h |
|------------|-------|----------|-------|--------|----------------------|------|
| | [V] | [A] | [W] | [%] | [mV _{p-p}] | [%] |
| RSP-750-5 | 5 | 0...100 | 500 | 2 | 150 | 82 |
| RSP-750-12 | 12 | 0...62,5 | 750 | 1 | 150 | 87 |
| RSP-750-15 | 15 | 0...50 | 750 | 1 | 150 | 89 |
| RSP-750-24 | 24 | 0...31,3 | 751,2 | 1 | 150 | 90,5 |
| RSP-750-27 | 27 | 0...27,8 | 750,6 | 1 | 150 | 90,5 |
| RSP-750-48 | 48 | 0...15,7 | 753,6 | 1 | 150 | 92 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | RSP75012 |
| Merk | MEANWELL |

