

GESCHAKELDE VOEDING SINGLE OUTPUT 50W 5V/10A

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



Beschrijving

MODEL RS-50-5

OUTPUT:

DC VOLTAGE 5.0V

RATED CURRENT 10A

CURRENT RANGE 0 ~ 10A

RATED POWER 50W

RIPPLE & NOISE (max.) 80mVp-p

OUTPUT VOLTAGE ADJ. RANGE 4.75 ~ 5.5V

VOLTAGE TOLERANCE +/-2.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-1.0%

SETUP, RISE TIME 500ms, 20ms/230VAC

HOLD TIME (Typ.) 60ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY(Typ.) 78%
AC CURRENT (Typ.) 0.8A/230VAC
INRUSH CURRENT (Typ.) COLD START 33A/230VAC
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power

Protection type : Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 5.75 ~ 6.75V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 99*97*36mm (L*W*H)

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | RS5005 |
| Merk | MEANWELL |
| Is on Sale | Nee |

