

GESCHAKELDE VOEDING SINGLE OUTPUT 15W 24V/0.625A

€ 13,95

Excl. BTW: € 11,53

Afbeeldingen



Beschrijving

Universal AC input / Full range
Protections: Short circuit / Overload / Over voltage / Over temperature
Cooling by free air convection
LED indicator for power on
100% full load burn-in test
All using 105C long life electrolytic capacitors
Withstand 300VAC surge input for 5 second
High operating temperature up to 70
Withstand 5G vibration test
High efficiency, long life and high reliability

MODEL RS-15-24
OUTPUT:
DC VOLTAGE 24V
RATED CURRENT 0.625A

CURRENT RANGE 0 ~ 0.625A
RATED POWER 15W
RIPPLE & NOISE (max.) 200mVp-p
OUTPUT VOLTAGE ADJ. RANGE 22 ~ 27.6V
VOLTAGE TOLERANCE +/-1.0%
LINE REGULATION +/-0.5%
LOAD REGULATION +/-0.5%
SETUP, RISE TIME 1000ms, 30ms/230VAC
HOLD TIME (Typ.) 70ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 82%
AC CURRENT (Typ.) 0.35A/230VAC
INRUSH CURRENT (Typ.) COLD START 65A/230VAC
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD Above 105% rated output power
Protection type : Hiccup mode, recovers automatically after fault condition is
OVER VOLTAGE 28.4 ~ 32.4V
Protection type : Shut down o/p voltage, recovers automatically after temperature goes down
Dimensions 99*82*36mm (L*W*H)

Productinformatie

Artikelnummer	RS1524
Merk	MEANWELL
Is on Sale	Nee

