

ACCU 12V 2.3A 178X35X61 900GR. AANSLUITING 4,8MM

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



Beschrijving

Features

- Powerful and maintenance-free lead-acid battery
- Absorbent glass mat technology
- Sealed, leak-resistant ABS container

Technical Specifications

| Part No. | U_N [V] | C_N [Ah] | Designed floating life [Years] |
|-------------|--------------|---------------|-----------------------------------|
| XPO.8-12AMP | 12 | 0,8 | 10 |
| XP1.2-12 | 12 | 1,2 | 3...5 |
| XP2.3-12 | 12 | 2,3 | 3...5 |

| | | | |
|-----------|----|------|--------|
| XP3.4-12 | 12 | 3,4 | - |
| XP7-12 | 12 | 7,08 | 5 |
| XP12-12F2 | 12 | 12 | 3...5 |
| XP18-12 | 12 | 18 | 3...5 |
| XP26-12 | 12 | 26 | 3...5 |
| XP45-12 | 12 | 45 | 12 |
| XP65-12 | 12 | 65 | 7...10 |

U_N = Nominal Voltage, C_N = Nominal Capacity (@ 25°C)

Dimensions, Weight and Connection

| Part No. | L x W x H [mm] | H _T [mm] | Weight [g] | Connection [mm] |
|-------------|-------------------|------------------------|---------------|-----------------------|
| XPO.8-12AMP | 96x25x62 | 62 | 330 | Plug AMP |
| XP1.2-12 | 97x43x52 | 58 | 540 | Flat Plug 4,8 |
| XP2.3-12 | 178x35x61 | 67 | 900 | Flat Plug 4,8 |
| XP3.4-12 | 134x67x60,5 | 66,5 | 1200 | Flat Plug 4,75 |
| XP7-12 | 151x65x94 | 100 | 2250 | Flat Plug 4,8/6,4 |
| XP12-12F2 | 151x98x95 | 101 | 3600 | Flat Plug 6,35/4,8 |
| XP18-12 | 181x77x167 | 167 | 5300 | Srew Terminal Ø5,5/M5 |
| XP26-12 | 165x176x127 | 127 | 7900 | Srew Terminal Ø5,5/M5 |
| XP45-12 | 197x165x170 | 170 | 14000 | Srew Terminal Ø6/M6 |
| XP65-12 | 350x167x179 | 186 | 20800 | Srew Terminal Ø8/M6 |

H_T = Total Height

Recycling

All used lead batteries must be given to an environmentally-friendly waste bank for disposal in accordance with local regulations.

Do not dispose of used batteries in domestic waste!

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | XP2.3-12 |
| Merk | XCELL |

