


GESCHAKELDE VOEDING SINGLE OUTPUT 198W 3.3V/60A

€ 69,95

Excl. BTW: € 57,81

Afbeeldingen



Beschrijving

Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile

Technical Specifications

Input Voltage:

88...264V AC (47...63Hz)

124...370V DC

Input Inrush Current, Max.:	40A
Leakage Current, Max.:	1mA
Output Voltage Adjustment:	±10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	900g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	U_{RN}	h
	[V]	[A]	[W]	[mV _{p-p}]	[%]
RSP-320-2.5	2.5	0...60	150	100	75,5
RSP-320-3.3	3.3	0...60	198	100	79,5
RSP-320-4	4	0...60	240	100	81
RSP-320-5	5	0...60	240	150	83
RSP-320-7.5	7.5	0...40	300	150	88
RSP-320-12	12	0...26,7	320,4	150	88
RSP-320-13.5	13,5	0...23,8	321,3	150	88
RSP-320-15	15	0...21,4	321	150	88,5
RSP-320-24	24	0...13,4	321,6	150	89
RSP-320-27	27	0...11,9	321,3	200	89
RSP-320-36	36	0...8,9	320,4	220	89,5
RSP-320-48	48	0...6,7	321,6	240	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	RSP32003
Merk	MEANWELL

