


GESCHAKELDE VOEDING SINGLE OUTPUT 90W 5V/18A

€ 25,95

Excl. BTW: € 21,45

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low profile
- Safety standards: EN 62368-1
- EMC standards: EN 55032 Class B and more
- 3 years manufacturer warranty



Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...373V DC

Input Inrush Current, Max.:	50A
Leakage Current, Max.:	0,75mA
Output Voltage Adjustment:	±10%
Over Load Protection:	110...150%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	1250V AC
Operating Temperature:	-30...+70°C
Operating Altitude, Max.:	5000m
Weight:	340g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U _A	I _A	P _A	DU _A	U _{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
LRS-100-3.3	3,3	0...20	66	3	100	84,5
LRS-100-5	5	0...18	90	2	100	86
LRS-100-12	12	0...8,5	102	1	120	88
LRS-100-15	15	0...7	105	1	120	88,5
LRS-100-24	24	0...4,5	108	1	150	90
LRS-100-36	36	0...2,8	100,8	1	200	90,5
LRS-100-48	48	0...2,3	110,4	1	200	91

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Artikelnummer	LRS10005
Merk	MEANWELL

