


GESCHAKELDE VOEDING SINGLE OUTPUT 300W 5.0V/60A

€ 119,00

Excl. BTW: € 98,35

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Built-in remote sense function
- DC OK signal



Technical Specifications



Input Voltage:	85...264V AC (47...63Hz)
	120...370V DC
Input Inrush Current, Max.:	70A
Leakage Current, Max.:	1,2mA
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-40...+70°C
Weight:	950g

I/P = Input, O/P = Output, FG = Frame Ground



U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Part Nr.	U_A	I_A	P_A	U_{adj}	DU_A	U_{RN}	h
	[V]	[A]	[W]	[V]	[%]	[mV _{p-p}]	[%]
HRP-300-3.3	3,3	0...60	198	2,8...3,8	2,5	80	80
HRP-300-5	5	0...60	300	4,3...5,8	2	90	82
HRP-300-7.5	7,5	0...40	300	6,8...9	2	100	86
HRP-300-12	12	0...27	324	10,2...13,8	1	120	88
HRP-300-15	15	0...22	330	13,5...18	1	150	88
HRP-300-24	24	0...14	336	21,6...28,8	1	150	87
HRP-300-36	36	0...9	324	28,8...39,6	1	250	88
HRP-300-48	48	0...7	336	40,8...55,2	1	250	89

 U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Artikelnummer	HRP30005
Merk	MEANWELL

