


## GESCHAKELDE VOEDING SINGLE OUTPUT 101W 7.5V/13.5A

€ 69,50

Excl. BTW: € 57,44

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Long life 105°C electrolytic capacitors
- Low no load power consumption
- Built-in remote On/Off control



#### Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

|                             |             |
|-----------------------------|-------------|
| Input Inrush Current, Max.: | 65A         |
| Leakage Current, Max.:      | 1mA         |
| Over Load Protection:       | 105...135%  |
| Withstand Voltage           |             |
| I/P-O/P:                    | 3000V AC    |
| I/P-FG:                     | 2000V AC    |
| O/P-FG:                     | 500V AC     |
| Operating Temperature:      | -40...+60°C |
| Weight:                     | 560g        |

I/P = Input, O/P = Output, FG = Frame Ground



| Part Nr.    | $U_A$ | $I_A$    | $P_A$ | $U_{adj}$   | $DU_A$    | $U_{RN}$             | $h$  |
|-------------|-------|----------|-------|-------------|-----------|----------------------|------|
|             | [V]   | [A]      | [W]   | [V]         | [%]       | [mV <sub>p-p</sub> ] | [%]  |
| HRP-100-3.3 | 3,3   | 0...20   | 66    | 3,1...3,8   | +2,5,-3,5 | 80                   | 78   |
| HRP-100-5   | 5     | 0...17   | 85    | 4,75...5,8  | 2,5       | 80                   | 83   |
| HRP-100-7.5 | 7,5   | 0...13,5 | 101,3 | 7,1...9     | 2,5       | 100                  | 84   |
| HRP-100-12  | 12    | 0...8,5  | 102   | 11,4...13,8 | 1,5       | 120                  | 87,5 |
| HRP-100-15  | 15    | 0...7    | 105   | 14,25...18  | 1,5       | 150                  | 88   |
| HRP-100-24  | 24    | 0...4,5  | 108   | 22,8...28,8 | 1,5       | 150                  | 88,5 |
| HRP-100-36  | 36    | 0...2,9  | 104,4 | 34,2...39,6 | 1,5       | 200                  | 89   |
| HRP-100-48  | 48    | 0...2,2  | 105,6 | 45,6...55,2 | 1,5       | 240                  | 90   |

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Productinformatie

---

|               |          |
|---------------|----------|
| Artikelnummer | HRP10007 |
| Merk          | MEANWELL |
| Is on Sale    | Nee      |

