


GESCHAKELDE VOEDING SINGLE OUTPUT 200W 7.5V/26.7A PFC

€ 99,95

Excl. BTW: € 82,60

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Built-in remote sense function

HRPG-200

Features

Same as HRP-200 but additional:

- Built-in remote On/Off control
- Low no load power consumption
- Built-in auxiliary power, Stand-by 5V/0,3A

Technical Specifications

Input Voltage:	85...264V AC (47...63Hz)
	120...370V DC
Input Inrush Current, Max.:	70A
Leakage Current, Max.:	1,2mA
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-40...+70°C
Weight:	770g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	U_{adj}	DU_A	U_{RN}	h
	[V]	[A]	[W]	[V]	[%]	[mV _{p-p}]	[%]
HRP-200-3.3	3,3	0...40	132	2,8...3,8	2	80	80
HRP-200-5	5	0...35	175	4,3...5,8	2	90	84
HRP-200-7.5	7,5	0...26,7	200,3	6,8...9	2	100	86
HRP-200-12	12	0...16,7	200,4	10,2...13,8	1	120	88

HRP-200-15	15	0...13,4	201	13,5...18	1	150	88
HRP-200-24	24	0...8,4	201,6	21,6...28,8	1	150	88
HRP-200-36	36	0...5,7	205,2	28,8...39,6	1	250	89
HRP-200-48	48	0...4,3	206,4	40,8...55,2	1	250	89
HRPG-200-3.3	3,3	0...40	132	2,8...3,8	2	80	80
HRPG-200-5	5	0...35	175	4,3...5,8	2	90	84
HRPG-200-7.5	7,5	0...26,7	200,3	6,8...9	2	100	86
HRPG-200-12	12	0...16,7	200,4	10,2...13,8	1	120	88
HRPG-200-15	15	0...13,4	201	13,5...18	1	150	88
HRPG-200-24	24	0...8,4	201,6	21,6...28,8	1	150	88
HRPG-200-36	36	0...5,7	205,2	28,8...39,6	1	250	89
HRPG-200-48	48	0...4,3	206,4	40,8...55,2	1	250	89

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Note

No load power consumption when Remote Control is off.
These power supplies are considered as a component that has to be installed in a final equipment.

Productinformatie

Artikelnummer	HRP20007
Merk	MEANWELL
Is on Sale	Nee

