


## GESCHAKELDE VOEDING SINGLE OUTPUT 450W 7.5V/60A PFC

€ 189,00

Excl. BTW: € 156,20

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Built-in remote sense function
- DC OK signal

#### Technical Specifications

Input Voltage:	85...264V AC (47...63Hz)
	120...370V DC
Input Inrush Current, Max.:	70A

Leakage Current, Max.:	1,5mA
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-40...+70°C
Weight:	1190g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	$U_A$	$I_A$	$P_A$	$U_{adj}$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[V]	[%]	[mV <sub>p-p</sub> ]	[%]
HRP-450-3.3	3,3	0...90	297	2,8...3,8	2	80	80
HRP-450-5	5	0...90	450	4,3...5,8	2	80	83
HRP-450-7.5	7,5	0...60	450	6,8...9	2	100	86,5
HRP-450-12	12	0...37,5	450	10,2...13,8	1	120	88
HRP-450-15	15	0...30	450	13,5...18	1	150	89
HRP-450-24	24	0...18,8	451,2	21,6...28,8	1	150	88
HRP-450-36	36	0...12,5	450	28,8...39,6	1	240	89
HRP-450-48	48	0...9,5	456	40,8...55,2	1	240	89,5

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

Artikelnummer	HRP45007
Merk	MEANWELL

