

Input Inrush Current, Max.:	30A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	-5/+10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	520g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
RSP-100-3.3	3,3	0...20	66	2	100	83
RSP-100-5	5	0...20	100	2	100	86
RSP-100-7.5	7,5	0...13,5	101,25	2	100	87
RSP-100-12	12	0...8,5	102	1	100	86
RSP-100-13.5	13,5	0...7,5	101,25	1	100	86,5
RSP-100-15	15	0...6,7	100,5	1	100	87
RSP-100-24	24	0...4,2	100,8	1	150	87
RSP-100-27	27	0...3,8	102,6	1	150	87
RSP-100-48	48	0...2,1	100,8	1	250	88

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Artikelnummer	RSP10024
Merk	MEANWELL



Productinformatie