


GESCHAKELDE VOEDING SINGLE OUTPUT 75W 24V/3.2A PFC

€ 47,89

Excl. BTW: € 39,58

Afbeeldingen



Beschrijving

Technical Specifications

Input Voltage:	85...264V AC (47...63Hz)
	120...370V DC
Input Inrush Current, Max.:	35A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	-5/+10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3750V AC

I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-25...+70°C
Weight:	440g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
RSP-75-3.3	3,3	0...15	49,5	2	80	76
RSP-75-5	5	0...15	75	2	80	82
RSP-75-7.5	7,5	0...10	75	2	80	84
RSP-75-12	12	0...6,3	75,6	2	120	85
RSP-75-13.5	13,5	0...5,6	75,6	2	120	85
RSP-75-15	15	0...5	75	2	120	86
RSP-75-24	24	0...3,2	76,8	1	120	87
RSP-75-27	27	0...2,8	75,6	1	120	88
RSP-75-48	48	0...1,6	76,8	1	200	89

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	RSP7524
Merk	MEANWELL

