


GESCHAKELDE VOEDING SINGLE OUTPUT 450W 24V/18.8A PFC

€ 189,00

Excl. BTW: € 156,20

Afbeeldingen



Beschrijving

Features

- Enclosed case, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Built-in remote sense function
- DC OK signal

Technical Specifications

Input Voltage:	85...264V AC (47...63Hz)
	120...370V DC
Input Inrush Current, Max.:	70A

Leakage Current, Max.:	1,5mA
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-40...+70°C
Weight:	1190g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	U_{adj}	DU_A	U_{RN}	h
	[V]	[A]	[W]	[V]	[%]	[mV _{p-p}]	[%]
HRP-450-3.3	3,3	0...90	297	2,8...3,8	2	80	80
HRP-450-5	5	0...90	450	4,3...5,8	2	80	83
HRP-450-7.5	7,5	0...60	450	6,8...9	2	100	86,5
HRP-450-12	12	0...37,5	450	10,2...13,8	1	120	88
HRP-450-15	15	0...30	450	13,5...18	1	150	89
HRP-450-24	24	0...18,8	451,2	21,6...28,8	1	150	88
HRP-450-36	36	0...12,5	450	28,8...39,6	1	240	89
HRP-450-48	48	0...9,5	456	40,8...55,2	1	240	89,5

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, U_{adj} = Output Voltage Adjustment, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	HRP45024
Merk	MEANWELL

