


## GESCHAKELDE VOEDING SINGLE OUTPUT 600W 24V/27A

€ 189,00

Excl. BTW: € 156,20

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Built-in cooling On/Off control
- Long life 105°C electrolytic capacitors
- Built-in remote sense function
- DC OK signal

#### Technical Specifications

|                             |                          |
|-----------------------------|--------------------------|
| Input Voltage:              | 85...264V AC (47...63Hz) |
|                             | 120...370V DC            |
| Input Inrush Current, Max.: | 70A                      |
| Leakage Current, Max.:      | 1,2mA                    |
| Over Load Protection:       | 105...135%               |
| Withstand Voltage           |                          |
| I/P-O/P:                    | 3000V AC                 |
| I/P-FG:                     | 2000V AC                 |
| O/P-FG:                     | 500V AC                  |
| Operating Temperature:      | -40...+70°C              |
| Weight                      |                          |
| HRP-600:                    | 1500g                    |

I/P = Input, O/P = Output, FG = Frame Ground

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

| Part Nr.    | $U_A$ | $I_A$    | $P_A$ | $U_{adj}$   | $DU_A$ | $U_{RN}$             | $h$  |
|-------------|-------|----------|-------|-------------|--------|----------------------|------|
|             | [V]   | [A]      | [W]   | [V]         | [%]    | [mV <sub>p-p</sub> ] | [%]  |
| HRP-600-3.3 | 3,3   | 0...120  | 396   | 2,8...3,8   | 2      | 100                  | 78,5 |
| HRP-600-5   | 5     | 0...120  | 600   | 4,3...5,8   | 2      | 100                  | 82   |
| HRP-600-7.5 | 7,5   | 0...80   | 600   | 6,8...9     | 2      | 100                  | 87   |
| HRP-600-12  | 12    | 0...53   | 636   | 10,2...13,8 | 1      | 120                  | 88   |
| HRP-600-15  | 15    | 0...43   | 645   | 13,5...18   | 1      | 150                  | 88   |
| HRP-600-24  | 24    | 0...27   | 648   | 21,6...28,8 | 1      | 150                  | 88   |
| HRP-600-36  | 36    | 0...17,5 | 630   | 28,8...39,6 | 1      | 200                  | 89   |
| HRP-600-48  | 48    | 0...13   | 624   | 40,8...55,2 | 1      | 240                  | 89   |

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Productinformatie

---

|               |          |
|---------------|----------|
| Artikelnummer | HRP60024 |
| Merk          | MEANWELL |

