


## GESCHAKELDE VOEDING SINGLE OUTPUT 100W 12V/8.5A PFC

€ 52,50

Excl. BTW: € 43,39

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Built-in remote On/Off control

#### Technical Specifications

Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

Input Inrush Current, Max.:	30A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	-5/+10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	520g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
RSP-100-3.3	3,3	0...20	66	2	100	83
RSP-100-5	5	0...20	100	2	100	86
RSP-100-7.5	7,5	0...13,5	101,25	2	100	87
RSP-100-12	12	0...8,5	102	1	100	86
RSP-100-13.5	13,5	0...7,5	101,25	1	100	86,5
RSP-100-15	15	0...6,7	100,5	1	100	87
RSP-100-24	24	0...4,2	100,8	1	150	87
RSP-100-27	27	0...3,8	102,6	1	150	87
RSP-100-48	48	0...2,1	100,8	1	250	88

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

---

Artikelnummer	RSP10012
Merk	MEANWELL



## Productinformatie